



Sil-Pad® Configurations


Imperial Measurements




4 Lead TO-66	Part Number Suffix	"A"	"B"	"C"	"D"	"E"	"F"	"G"
	-84	1.312	.762	.140	.062	.960	.200	.100




Plastic Power	Part Number Suffix	Dimensions				Part Number Suffix	Dimensions				
		"A"	"B"	"C"	"D"		"A"	"B"	"C"	"D"	
Various (Clip Mount)	-35	.710	.500	.160	.141	Various	-104	1.000	.750	.300	.140
	-43	.750	.500			Various	-107	.810	.910	.170	.147
	-50	.437	.312	.140	.093	Various	-110	.984	.787		
	-51	.687	.562	.218	.125	Various	-114	.827	.945	.197	.150
	-52	.855	.630	.230	.093	Various	-116	.855	.630	.228	.122
	-58	.750	.500	.187	.147	Various	-117	.827	.709	.256	.126
	-55	.610	.560	.245	.125	Various	-118	.748	.551	.217	.126
	-56	.855	.562	.218	.125	Various	-119	.437	.311	.142	.110
	-58	.750	.500	.187	.125	Various	-120	.728	.472	.157	.098
	-60	.437	.312	.140	.122	TO-3P	-122	1.140	.810	.355	.147
	-61	.750	.410	.225	.156	Various	-126	.945	.748	.256	.162
	-62	.750	.600	.240	.150	Various	-128	.984	1.654	.315	.157
	-63	.750	.600	.240	.115	Various	-131	.709	.512	.177	.122
	-64	.500	.385	.170	.120	Various	-132	.472	.315	.157	.126
	-68	1.125	.625	.200	.145	Various	-133	.866	.709	.256	.126
	-70	1.410	.810	.355	.147	Various	-134	.945	.709	.228	.126
	-90	.860	.740	.200	.160	Various	-136	1.250	1.000		
	-102	.866	.650	.217	.142	Various	-137	1.250	1.000	.258	.127
	-103	.750	.800	.150	.160	Various	-138	1.250	1.000	.258	.148




Power Module	Part Number Suffix	Dimensions					
		"A"	"B"	"C"	"D"	"E"	"F"
	-67	1.500	.900	.150	1.200	.450	.075
	-101	2.500	2.000	.344	1.812	1.000	.156




Plastic Power	Part Number Suffix	Dimensions						
		"A"	"B"	"C"	"D"	"E"	"F"	"G"
	-57	.910	.500	.200	.125	.580	.046	.265
	-89	.983	.750	.432	.156	.665	.101	.217




Plastic Power	Part Number Suffix	Dimensions							
		"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"
	-66	1.000	.500	.200	.141	.626	.046	.219	.032



Power Resistors	Part Number Suffix	Dimensions									
		"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"	"I"	
	RH-25	-.94	1.187	1.205	.234	.469	.212	.156	.719	.781	.140
	RH-50	-.95	2.093	1.265	.265	.530	.210	.255	1.563	.845	.140
	RH-5	-.96	.725	.771	.140	.280	.140	.156	.445	.491	.093
	RH-10	-.97	.805	.890	.127	.250	.130	.190	.551	.630	.121
	RH-25	-.98	1.150	1.180	.231	.425	.190	.270	.688	.800	.147
	RH-50	-.99	1.965	1.236	.198	.404	.132	.263	1.569	.972	.130



TO-220 Multiples	Part Number Suffix	Dimensions						# of Holes
		"A"	"B"	"C"	"D"	"E"	"F"	
2 Parts	-34	1.000	.750	.187	.125	.250	.500	2
3 Parts	-36	1.500	.750	.187	.125	.250	.500	3
	-37	2.000	.750	.187	.125	.250	.500	4
	-38	2.500	.750	.187	.125	.250	.500	5
	-39	3.000	.750	.187	.125	.250	.500	6
	-40	3.500	.750	.187	.125	.250	.500	7
	-41	4.000	.750	.187	.125	.250	.500	8




Power Module	Part Number Suffix	Dimensions					
		"A"	"B"	"C"	"D"	"E"	"F"
	-108	4.600	2.400	2.125	.500	1.800	.125
	-140	4.598	2.402	2.098	0.500	1.799	0.150
	-141	2.279	2.402	2.102	0.488	0.650	0.150
	-142	2.280	1.450	1.270	0.490	0.650	0.130


ORDERING

Sil-Pad® Configurations


Imperial Measurements




Part Number	Part Number Suffix	"A"	"B"	Dimensions		
		"A"	"B"	"C"	"D"	"E"
Multiwatt	-124	.872	.790	.160	.148	.118 x 45°
	-125	.866	.787	.157	.154	.079 x 45°




Part Number	Part Number Suffix	"A"	"B"	"C"	"D"	"E"	"F"
Multi-Lead TO-66	-93	1.350	.800	.140	.400	.960	.480




Part Number	Part Number Suffix	Dimensions		Part Number Suffix	Dimensions	
		"A"	"B"			"B"
Diode Washer	-19	.510	.140	Various	-.75	.360 .260
	-20	.510	.200	Various	-.76	.750 .125
	-21	.800	.260	Various	-.77	.800 .190
	DO-4 (oversized)	.625	.200	DO-8	-.78	.875 .313
	DO-5 (oversized)	1.000	.260	Various	-.79	1.180 .515
	Various	.812	.145	Various	-.80	1.250 .380
	Various	.812	.115	Various	-.81	1.500 .200
	Various	1.000	.140	Various	-.82	.512 .161
	Various	1.500	.500	Various	-.111	.591 .217




Part Number	Part Number Suffix	Dimensions		
		"A"	"B"	"C"
TO-36	-08	1.063	.690	.190




Part Number	Part Number Suffix	Dimensions		
		"A"	"B"	"C"
Small Power Devices	TO-5, 3 Holes	-.09	.360	.200 .040
	TO-18, 3 Holes	-.12	.250	.100 .036
	TO-18, 4 Holes	-.13	.250	.100 .036
	TO-5, 4 Holes	-.33	.360	.200 .040
	TO-5, 3 Holes	-.44	.390	.200 .040
	TO-5, 4 Holes	-.45	.390	.200 .040




Part Number	Part Number Suffix	Dimensions		
		"A"	"B"	"C"
Rectifier	-46	1.250	1.250	.200
	-47	1.125	1.125	.140
	-48	1.000	1.000	.187




Part Number	Part Number Suffix	"A"	"B"	Dimensions		
		"A"	"B"	"C"	"D"	"E"
TIP Packages	Clip Mount TIP-36	-.42	.984	.787		.205
	Plastic Tip TO-3P	-.53	.865	.650	.650	.140 .205
	Plastic Clip	-.73	.984	.787	.708	.142 .205




Part Number	Part Number Suffix	Dimensions						
		"A"	"B"	"C"	"D"	"E"	"F"	"G"
Power Module	-100	2.510	1.260	.630	.305	1.900	.205	.205
	-123	1.614	1.102	.551	.157	1.220	.118	.118



Part Number	Part Number Suffix	Dimensions						
		"A"	"B"	"C"	"D"	"E"	"F"	"G"
SIP Package	-105	1.450	.838	.612	.245	.960	.170	.120



Part Number	Part Number Suffix	Dimensions			
		"A"	"B"	"C"	"D"
Quartz	-115	.472	.197	.193	.031




Part Number	Part Number Suffix	Dimensions						
		"A"	"B"	"C"	"D"	"E"	"F"	"G"
Power Module	-109	1.350	.642	.321	.195	.960	.060	.125

Sil-Pad® Configurations


Imperial Measurements

TO-3 & TO-66


Style	Part Number Suffix	"A"	"B"	Dimensions		"E"	"F"	"G"
				"C"	"D"			
	-02	1.780	1.250	.140	.093	1.187	.430	.072
	-03	1.563	1.050	.140	.080	1.187	.430	.072
	-04	1.650	1.140	.122	.062	1.187	.430	.072
	-05	1.650	1.140	.140	.093	1.187	.430	.072
	-06	1.650	1.140	.165	.062	1.187	.430	.072
	-07	1.780	1.250	.165	.094	1.187	.430	.072
	-10	1.440	1.000	.140	.075	.960	.200	.100
	-11	1.312	.762	.140	.062	.960	.200	.100
	-15	1.780	1.250	.140	.046	1.187	.430	.072
	-16	2.070	1.560	.122	.062	1.187	.430	.072
	-17	1.650	1.140	.140	.046	1.187	.430	.072
	-18	1.563	1.050	.140	.140	1.187	.430	.072
	-23	1.593	1.100	.156	.062	1.187	.430	.072
	-24	1.700	1.187	.156	.062	1.187	.430	.072
	-29	1.650	1.065	.140	.046	1.187	.430	.072
	-30	1.250	.700	.140	.062	.960	.200	.100
	-31	1.375	.825	.140	.062	.960	.200	.100
	-59 Leadless	1.650	1.140	.165		1.187		
	-112	1.780	1.248	.165	.063	1.185	.429	.073
	-113	1.563	1.051	.165	.079	1.185	.429	.073
	-127	1.307	.819	.165	.063	.909	.236	.061
	-129	1.654	1.063	.138	.059	1.181	.433	.071
	-135	1.650	1.142	.165	.142	1.187	.429	.072




3 Lead TO-3	Part Number Suffix	"A"	"B"	Dimensions		"E"	"F"	"G"	"H"	"I"
				"C"	"D"					
	-92	1.650	1.140	.140	.093	1.187	.430	.400	.155	.718




4 Lead TO-3	Part Number Suffix	"A"	"B"	Dimensions		"E"	"F"	"G"
				"C"	"D"			
	-86	1.560	1.050	.156	.080	1.170	.470	72°
	-87	1.563	1.050	.156	.063	1.187	.470	72°




8 Lead TO-3	Part Number Suffix	"A"	"B"	Dimensions		"E"	"F"	"G"
				"C"	"D"			
	-88	1.655	1.187	.156	.060	1.187	40°	.500




10 Lead TO-3	Part Number Suffix	"A"	"B"	Dimensions		"E"	"F"	"G"	"H"
				"C"	"D"				
	-91	1.650	1.140	.165	.040	1.187	.593	.500	32.7°



3 Lead TO-66	Part Number Suffix	"A"	"B"	Dimensions		"E"	"F"	"G"	"H"
				"C"	"D"				
	-85	1.275	.750	.156	.100	.960	.200	.100	.200



9 Lead TO-66	Part Number Suffix	"A"	"B"	Dimensions		"E"	"F"	"G"	"H"
				"C"	"D"				
	-83	1.440	1.000	.140	.055	.960	.480	.325	36°



Power Module	Part Number Suffix	"A"	"B"	Dimensions		"E"
				"C"	"D"	
	-130	1.600	.480	.165	1.197	.240

