



NOTES:

1. TOLERANCE ± 0.015 UNLESS NOTED OTHERWISE.
2. TOP CONDUCTIVE LAYER TO BE .007' THICK POLYESTER WITH A ANTI-GLARE COATING.
3. THE CONNECTOR IS LOCATED ON THE LEFT SIDE OF THE PANEL.
4. PIN ONE LOCATION IS THE TOP PIN WHEN VIEWING WITH CABLE TO THE LEFT.
5. PINOUT TO BE AS INDICATED.
 PIN 1 - UPPER RIGHT,
 PIN 2 - LOWER RIGHT,
 PIN 3 - PLANE,
 PIN 4 - UPPER LEFT,
 PIN 5 - LOWER LEFT.
6. TAIL TO BE TERMINATED USING: AMP RECEPTACLE 2-487406-4 OR EQUIVALENT
7. HOUSING TO BE AMP PART NUMBER 487378-4 OR EQUIVALENT
8. TOTAL PANEL THICKNESS TO BE 0.126 ± 0.008 ' NOMINAL.

BERGQUIST TOUCH PRODUCTS			
301 WASHINGTON STREET, CANNON FALLS, MN 55009			
TITLE: 19.2' DIAGONAL 5 WIRE TOUCHSCREEN			
DRN: MLR	DATE: 12/17/07	SCALE: 1:1	TOL: ± 0.015
CHKD:	DATE:	PART NUMBER: 400392	REV: -
APVD:	DATE:		